

Clark County Comprehensive Planning Department Title 30 Commercial and Industrial Checklist

		TITI F	30 COD	E SECTI	ONS					Y N NA
30.02 ZONING DISTRICTS		11166	30 000	LOLUII	0110					I IN INA
	CN60	CP60	CG60	CC75	CU	CR	IP80	IL80	IH80	
Lot Coverage Max % Yard Setbacks Front	10	15	10	10	10	10	20	20	20	
Side Street (Corner)	10	10	10	10	10	10	20	20	20	
	35	35	50	55	200		50	50	75	
Height Meet Density (if applicable) Che			30	33	200		50	30	73	
Architectural Intrusions/Enclos			ata catha	ok up to 1	l' hut no	loce tha	n 5' to pro	norty line	o (3 IE DI DC)	
	ABO		AEO *			NPO	PCO		` '	
Check SLUCM for AE r	_	_	_	про	IVIPO	NPO	PCO	RRO	SMO	
			00.02-7							
30.03.03 USES: Confirm	any cond	Itions								
30.04.01 LANDSCAPE PLAN		ما المالية	Outda							
Existing Trees to Scale See Lar	idscape ir	istaliation	Guide							
Significant Trees Preserved										
Any Trees Removed (by canop				f	li a i a a ta al	o: 0 o				
All Required Landscaping with		spatiai co	nsiderali	on ior an	licipated	Size a Si	Jieau			
Private Streets – plan not require										
30.04.01 D LANDSCAPE STAND		I !-4/A I4-				·!		\		
Plants on SNWA/SNRPC Regio					a protess	sionai (no	ot size sw	(ap)		
Turf? ONLY Cemeteries, Parks,										
Sight Zones SEE 30.04.08 G do								/	2D Altamatica	
Street LS for Detached SW 15's										
Street LS for Attached SW 10's									JR Alternative	
Parking LS – Option 1: 1 L Tree		every 6 8	k end of r	ow/Optio	n 2 – stri	p every '	12 and er	id of row		
30.04.02 BUFFER STANDARDS										
							OR PF	ADJ U	RBAN FWAY	
8' wall with 15' wide LS strip with	2 rows of	evergreei	n trees pl	anted 20	apart of	tset				
30.04.03 FENCES AND WALLS										
Fences and Walls FRONT	3' MAX									
Fences and Walls 8' COMM/10'										
Materials brick, stone, stucco, wr										
Retaining Walls 3' by right *6' if the				if 3' heigh	nt with 3'	horizont	al landsca	aped		
Security Fencing Industrial 10' n	nax/wire 8	' above g	round							
Access Gate 50' lip of gutter										
Egress Gate 20' lip of gutter										
Guard Enclosure 50' ROW line										
Individual Gated Property – ope	en during b	ousiness l	nours/set	back 18'	PL OR IF	NOT 50	o' from Pl			
30.04.04 PARKING										
Parking Table 30.04-2 (# Req) /	Exceed 15	5% Max (I	NOT INC	: on stree	et, ada, c	arpool, E	V, fleet, I	oading, s	structured)	
Cart Collection Separate										
Drive Thru Residential Adjacen										
Reduction (%) 20 Total (+Sustainab					/laryland F	Pkwy up t	o 25 / Aff F	Hsg 25 / E	xisting 10	
Demand Study for more / less pa	arking qua	ntities Tra	affic Engi	neer						
On Street Parking										
Shared/Offsite max 150' from PL	along pe	d route/no	o arterial	separatir	g/formal	agreeme	ent betwe	en owne	rs/documented	
Access no backing out Driveways	distinct									
Interior Configuration no conflic										
Paving No waivers to Title 30. Me	eet DES (r	not req for	r seasona	al sales, s	special ev	vent, stal	ole)			
Paving and Striping REQ IN Hyd										
Pedestrian Walkways REQ										
Parking Layout 30.04-3 AND Di		20.04.4								



Clark County Comprehensive Planning Department Title 30 Commercial and Industrial Checklist

Tandem Parking	
EV Charging Spaces – 30.04-5	
ADA 30.04-6 medical care mobility 20% / outpatient medical 10% / mf bldg. ADA units 2%	
Loading 30.04-7 to 15k-0/15kto25k-1/over 25k- 1 space + 1 ea addtl fraction of 25k above 1st 25k +Res Adj (+Alternative)	
Bicycle Parking 30.04-8 (most req 4 spaces min)(Exempt: SFR, dev in nonurban area, LVBS Sah-Russell & Resort Hotel	
30.04.05 SITE DESIGN	
Offsite Pedestrian Connectivity SW	
Onsite Pedestrian Connectivity on-site/parking lot/building entrances/adjacent transit stops/internal walk to SW	
Walkways/Crosswalk change materials/bollards/raised median walkways w/ls/stamped or stained concrete	
Trails	
Foundation Masking	
Screening Mechanical Equipment – Ground past height by 1': can use fence/wall: arch features integrated	
Roof Mounted – visible within 100' screened to height of equip: integrated into building/similar materials	
Trash Enclosure 30.04-7	
Building Materials Glass, masonry, metal, stucco, and wood.	
Accessory Uses and Structures – zoning district setback/complementary colors materials	
30.04.05 DESIGN STANDARDS	
Four-Sided Arch no blank walls	
ARTICULATION Horizontal Ea 50' at least 2: roofline vary 2'+/ wall/plane change 1'/window	
ARTICULATION Vertical 2 stories ↑ identifiable base, middle, top	
Entrances face street frontage (not multi)/primary entrance articulated pediments, columns, porticos, porches	
Cross Access	
Drive Thru(s) separate from drive aisle or ped/adequate stacking and Res ADJ 30.04.06 AND 200' separation	
Overhead Doors rear of property, internal to development, screened from ROW	
30.04.05 J SUSTAINABILITY 7 POINTS REQUIRED Use Worksheet and Site Plan Example	
30.04.05 K Hillside Development	
30.04.06 RESIDENTIAL ADJACENCY	
13U.U4.U0 RESIDENTIAL ADJAGENGT	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use.	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200'	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev W/in, abut, adj, RNP NPO 10,000k lots Res Dev structures W/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25%	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent mp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg, dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50'	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50' Parking: along lot lines adjacent to non-res dev/side of corner lot facing primary frontage/behind building/adj res	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50' Parking: along lot lines adjacent to non-res dev/side of corner lot facing primary frontage/behind building/adj res Parking Screening w/in 30' & no buffer: 15' buffer double row evergreen 20' offset ctr OR LS, berm/dec wall 8'	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50' Parking: along lot lines adjacent to non-res dev/side of comer lot facing primary frontage/behind building/adj res Parking Screening w/in 30' & no buffer: 15' buffer double row evergreen 20' offset ctr OR LS, berm/dec wall 8' Cut through traffic discouraged	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent mp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg, dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50' Parking: along lot lines adjacent to non-res dev/side of corner lot facing primary frontage/behind building/adj res Parking Screening w/in 30' & no buffer: 15' buffer double row evergreen 20' offset ctr OR LS, berm/dec wall 8' Cut through traffic discouraged Roll up doors must be screened by another building to face residential	
Vehicular Access – no res local street/block along arterial, collector, or local is master planned SFR unless sole NO primary PA or Outside Storage Grading: 3 feet of fill minimum 5' from shared PL, 6 feet fill min 20' from shared PL, 9 feet fill min 50' from shared PL Res Dev w/in, abut, adj, RNP NPO 10,000k lots Res Dev structures w/in, adj, RNP NPO do not exceed RNP Side/Rear Setback of the adjacent rnp npo along shared lot lines Higher activity areas not adjacent to residential/OR require Buffer 30.04.02 Adjacent side/rear setbacks match RNP NPO Tallest/largest structures multi bldg. dev. sited within core decreased building mass next to res Nonresidential uses prohibited adjacent residential if horizontal mixed use. Height Step Backs 1' horiz step back ea ft over 35'. No part shall exceed 60' w/in 100' of SFR/D or 100' w/in 200' Signs 30.04.06I no illuminated signs rear/side facing adjacent residential Illuminated Wall Signs front minimize visibility and internally illuminated not orient toward res No illumination within 100' of an area subject to Res Adj Electronic Message units reduce by 25% Freestanding max 20'/not within 60'/over an acre site Exterior lighting 18' max Trash Enclosure/Recycling not within 50' Parking: along lot lines adjacent to non-res dev/side of corner lot facing primary frontage/behind building/adj res Parking Screening w/in 30' & no buffer: 15' buffer double row evergreen 20' offset ctr OR LS, berm/dec wall 8' Cut through traffic discouraged	



Clark County Comprehensive Planning Department Title 30 Commercial and Industrial Checklist

Loading Spaces for more than 1 space/dock shall set back 150'				
Loading Areas require buffer screen from residential 30.04.02				
Lighting – security motion sensor on no more than 12 minutes				
Lighting Shielded – project downward				
Lighting warm lighting. No white or blue				
Lighting max 25' freestanding luminaries (Rec lighting not included)				
Noise D				
30.04.10 NONESSENTIAL WATER FEATURES				
Swimming Pool – 4% first 10 acres or less & 0.4% additional above 10/Resorts additional 5 sf ea guest room				
Ornamental Water Feature – resort hotel abatement with purveyor				