



# Clark County Department of Building & Fire Prevention

4701 W. Russell Rd ~ Las Vegas NV 89118  
(702) 455-3000 ~ Fax (702) 221-0630

Jerome A. Stueve, P.E., Director  
Samuel D. Palmer P.E., Assistant Director • Girard W. Page, Fire Marshal

Report No.	
Page	of
Inspection Date	
Permit No.	

## POST-INSTALLED ADHESIVE ANCHORAGE CLEARANCE REPORT

Project Address:		Lot:		Block:	
Development Name:					
Quality Assurance Agency:		Owner/Agent:			
<b>Owner/Agent Signature:</b>					Date:
CCBD Inspector Initials					Date:

### 1<sup>st</sup> INSTALLATION INSPECTION SUMMARY

INSPECTION ITEM	RESULTS	INSPECTION ITEM	RESULTS
CCBD Plan Approval Date:		Quantity of Rods/Bolts Installed:	
CCBD Plan Sheet & Detail		Hole Depth & Diameter:	
Adhesive Product Name:		Anchor Diameter, Type & Length:	
Adhesive Expiration Date:		Anchor Embedment Depth:	
Evaluation Report No. & Date:		Anchor Spacing	
Concrete Type and Strength		Anchor Edge Distance	
Concrete Thickness & Temp (°F)		Time of Installation & t cure, full (time till full cure)	
Hole Cleaning Procedure			

The special inspector must be present at the time the bolt is torqued.

### LOCATIONS OF ROD/BOLT & ADDITIONAL INSPECTION INFORMATION


**I hereby acknowledge that I have reviewed the approved plans, applicable evaluation report, and manufacturers' installation instructions. I inspected the products and observed the product installation. The anchor installation has been verified to be in accordance with the manufacturer's published instructions, the above referenced evaluation report and the Clark County approved plans.**

SPECIAL INSPECTOR (PRINTED)	
SPECIAL INSPECTOR (SIGNATURE)	DATE

ENGINEER STAMP HERE

Return completed certification to Clark County Building Department

Use of this form serves as a Quality Assurance Agency Special Inspection Agreement between Building Official, Owner and Quality Assurance Agency for the purposes of special inspection per Section 22.02.515 of the Building Administrative Code of Clark County.



# Clark County Department Of Building & Fire Prevention

4701 W. Russell Rd ~ Las Vegas NV 89118  
(702) 455-3000 ~ Fax (702) 221-0630

Jerome A. Stueve, P.E., Director  
Samuel D. Palmer P.E., Assistant Director • Girard W. Page, Fire Marshal

Report No.	
Page	of
Inspection Date	
Permit No.	

## POST-INSTALLED ADHESIVE ANCHORAGE CLEARANCE REPORT

Project Address:		Lot:		Block:	
Development Name:					
Quality Assurance Agency:		Owner/Agent:			
<b>Owner/Agent Signature:</b>					Date:
CCBD Inspector Initials					Date:

## 2<sup>nd</sup> INSTALLATION INSPECTION SUMMARY

INSPECTION ITEM	RESULTS
Time of Torquing & t cure (time elapsed)	
Quantity Installed & Type:	
Tightening Torque for Each Bolt	
Reference the 1 <sup>st</sup> Installation Inspection Summary Reports	
Serial Number of the Torque Wrench and Date of Calibration	

The special inspector must be present at the time the bolt is torqued.

## LOCATIONS OF ROD/BOLT & ADDITIONAL INSPECTION INFORMATION


**I hereby acknowledge that I have reviewed the approved plans, applicable evaluation report, and manufacturers' installation instructions. I inspected the products and observed the product installation. The anchor installation has been verified to be in accordance with the manufacturer's published instructions, the above referenced evaluation report and the Clark County approved plans.**

ENGINEER STAMP HERE

SPECIAL INSPECTOR (PRINTED)	
SPECIAL INSPECTOR (SIGNATURE)	DATE

Return completed certification to Clark County Department of Building & Fire Prevention

## **POST-INSTALLED ADHESIVE ANCHOR CLEARANCE PROCEDURE** **SPECIAL CASES: C-E**

THIS FORM IS AVAILABLE AT THE CLARK COUNTY DEPARTMENT OF BUILDING & FIRE PREVENTION WEB SITE AND LISTED PRIME AGENCIES

1. The clearance report shall be used for post installed adhesive anchorage systems as identified in the approved plans and used as an alternate to the specified cast-in-place anchor.
2. The quality assurance agency special inspector shall complete the report for the work performed and leave a copy with the general contractor or permit holder. (At this point an engineer from the special inspection agency will not have sealed the report.)
3. The special inspector must be present at the time the bolt is torqued.
4. After the 1<sup>st</sup> and 2<sup>nd</sup> inspection has been completed, the report shall be given to the Clark County Building (CCDBFP) Inspector as assurance that adhesive anchorage system installations have been inspected and accepted by the Quality Assurance Agency (QAA), prior to or at shear wall inspection.
5. The CCDBFP inspector shall initial the reports then place the reports into a designated basket in the inspections office. The designated basket will be located at the public counter.
6. A Building Permit Specialist shall enter the clearance requirement for adhesive anchorage into the required inspection screen for the permit listed on the form. The clearance shall be established at the hold point prior to a framing inspection.
7. The structural group will review and disposition the engineer sealed adhesive anchorage report. Both the field copies and the engineered sealed copies must be received by CCDBFP staff prior to the removal of the hold point.
8. The engineer sealed reports form shall be sent to CCDBFP records by the CCDBFP staff.

### **Adhesive Anchorage of Rods/Bolts Form**

Go to our web site and select forms.

<http://www.clarkcountynv.gov/building>