

4701 W. Russell Rd Suite 200 Las Vegas, NV 89118-2231 Phone (702) 455-5942 Fax (702) 383-9994

For DAQ Use Only	

AQR 103: MISCELLANEOUS METAL OR PLASTIC PARTS COATING OPERATIONS EMISSIONS CALCULATION WORKSHEET

This Emissions Calculation Worksheet is not a mandatory form. The applicant may use a custom worksheet when submitting a registration or permit application.

Source ID/Registration Number (not applicable for new source	es):		
Company name:			
Source (facility) name:			
Source (facility) address:			
City, state, ZIP:			
Mailing address (if different from source address):			
Projected Maximum Emissions (PME) means the higher source is projected to emit VOC based on anticipated prorates that does not include emission reductions from add-To calculate the PME, enter the maximum projected usage another sheet if you have more products than can be listed.	oduction, throu on controls.	ighput, heat input, or m	naterial utilization
Material/Product Used	Usage (gal)	VOC Content (lb/gal)	PME (ton/yr)
	0 (0 /	, G /	· · · · ·
PME (in	tons/year) from	additional sheets, if any:	
FA	ACILITY TOT	AL PME (in tons/year):	
		, ,	
Emissions Control System (ECS): If you are using an the control efficiency below. For more information on E		-	· ·
ECS control efficiency:%			

document is true, accurate and complete.	formation contained in this		
Owner, Operator, or Responsible Official Certification (original signature)		Date	
Printed Name			
Office Phone:	Cellphone:		
Email Address:			

Please complete this form electronically to the best of your ability. Submit the completed report with the Owner's, Operator's, or Responsible Official's original (wet) signature to the Division of Air Quality by mail or in person at the address listed above.

Directions for completing the form manually:

- PME is calculated based on the projected maximum usage and the VOC content of the individual products summed for the entire source.
- To calculate VOC PME from each product or material usage:
 - Start with the maximum amount of VOC-containing material (in gallons) used during a calendar year. Multiply this value by the VOC emission factor (lb/gal) provided in the Environmental or Safety Data Sheets (SDS) or records for the material and divide the result by 2000; this is the VOC PME in tons/year for the material. Do this for each material. Add the individual PMEs to get the total source PME. You may also attach a computer-generated log of actual product consumption and VOC emissions.

gallons/year \times pounds/gallon = pounds \div 2000 = tons/year	ar of	VOC	PI	VIE
--	-------	-----	----	-----

If you have any questions or need clarification on completing this form, please contact the Air Quality Small Business Assistant Program at (702) 455-5942.