



4701 W. Russell Rd Suite 200 Las Vegas, NV 89118-2231 Phone (702) 455-5942 Fax (702) 383-9994

## AQR 106: OFFSET LITHOGRAPHIC LETTERPRESS, AND FLEXIBLE PACKAGE PRINTING AND OTHER GRAPHIC ARTS OPERATIONS EMISSIONS CALCULATION WORKSHEET

This Emissions Calculation Worksheet is not a mandatory form. The applicant may use a custom worksheet when submitting a registration or permit application.

Source ID/Registration Number (not applicable for new sources):
Company name:
Source (facility) name:
Source (facility) address:
City, state, ZIP:
Mailing address (if different from source address):

**Projected Maximum Emissions** (PME) means the highest annual rate, in tons per year, at which the stationary source is projected to emit VOC based on anticipated production, throughput, heat input, or material utilization rates that does not include emission reductions from add-on controls.

To calculate the PME, enter the maximum projected usage, VOC content, and retention factor of each material. Copy this table on another sheet if you have more products than can be listed here.

Material/Product Used	Usage (gal)	VOC Content (lb/gal)	Retention Factor <sup>1</sup> (RF) (%)	PME (ton/yr)
<b>PME</b> (in tons/year) from additional sheets, if any:				
FACILITY TOTAL PME (in tons/year):				

<sup>1</sup> A Retention Factor is the amount of material that adheres to the media and is not emitted.

**Emissions Control System (ECS):** If you are using an ECS to comply with Section 106 requirements, enter the control efficiency below. For more information on ECS, refer to Section 106 and the Fact Sheet.

ECS control efficiency:

I certify that, based on information and belief formed after reasonable inquiry, the information contained in this document is true, accurate and complete.

Owner, Operator, or Responsible Official Certification (original	l signature)	Date
Printed Name		
Office Phone:	Cellphone:	
Email Address:		

Please complete this form electronically to the best of your ability. Submit the completed report with the Owner's, Operator's, or Responsible Official's original (wet) signature to the Division of Air Quality by mail or in person at the address listed above.

## **Directions for completing the form manually:**

- PME is calculated based on the projected maximum usage and the VOC content of the individual products summed for the entire source.
- To calculate VOC PME from each product or material usage:
  - Start with the maximum amount of VOC-containing material (in gallons) used during a calendar year. Multiply this value by the VOC emission factor (lb/gal) provided in the Environmental or Safety Data Sheets (SDS) or records for the material and divide the result by 2000; this is the VOC PME in tons/year for the material. Do this for each material. Add the individual PMEs to get the total source PME. You may also attach a computer-generated log of actual product consumption and VOC emissions.

\_\_\_\_\_ gallons/year × \_\_\_\_\_ pounds/gallon = \_\_\_ pounds ÷ 2000 = \_\_\_\_ tons/year of VOC PME

If you have any questions or need clarification on completing this form, please contact the Air Quality Small Business Assistant Program at (702) 455-5942.